

Tabla de selección

		designación	TR 600 black	TR 600 blue	TR 600 red	TR 600 yellow	TR 600 CY black	TR 600 CY blue	TR 600 CY Lean	TR 600 Auto black	TR 600 Auto blue	TR 600 Auto red	TR 600 Auto CY black	TR 600 HD	TR 600 C HD	TR 249
construcción básica	conductores numerados		●	●	●	●	●	●	●	●	●	●	●	●	●	
	código identificación a imitación US 2						●	●	●				●			●
	apantallado						●	●					●		●	
	cubierta interior						●	●					●		●	
rango de temperatura	+105 °C		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	+ 90 °C		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	- 25 °C		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	- 40 °C		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Cold Bend Test - 40 °C													●	●	
tensión	Tensión UL-AWM 600 V		●	●	●	●	●	●	●	●	●	●	●	●	●	
	Tensión (UL) / c(UL) 600 V		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Tensión (UL) WTTC 1000 V		●	●	●	●	●	●	●	●	●	●	●	●	●	
	Tensión CSA-AWM 1000 V		●													
	Tensión de prueba 2000 V													●	●	
	Tensión de prueba 18-10 AWG 3000 V															●
	Tensión de prueba 8- 2 AWG 3500 V															●
	Tensión de prueba 18-10 AWG 6000 V		●	●	●	●	●	●	●	●	●	●	●			
normas	Tensión de prueba 8- 2 AWG 7500 V		●	●	●	●	●	●	●	●	●	●	●			
	Comportamiento en combustión (UL) FT4		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Comportamiento en combustión c(UL) FT1, FT2, FT4		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Comportamiento en combustión CSA FT1, FT2		●													
	aprobación UL		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	aprobación (UL)		●	●	●	●	●	●	●	●	●	●	●	●	●	●
particularidad	aprobación c(UL)us		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	aprobación CSA		●											●	●	
	Resistencia al aceite I		●	●	●	●	●	●	●	●	●	●	●			●
	Resistencia al aceite I + II													●	●	
	Resistencia a UV		●	●	●	●	●	●	●	●	●	●	●			●
	Exposed Runs		●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Direct Burial		●	●	●	●	●	●	●	●	●	●	●			●
	Machinery Area		●	●	●	●	●	●	●	●	●	●	●			●

