

THERMOCOUPLES

RING THERMOCOUPLE T224



■ For the temperature collection at surfaces. Easy mounting with the help of a screw and appropriate for numerous application fields. The stainless steel wire armouring of the connection cable is used as mechanical protection.



Also available in type K, T or L*
and classes 1 or 2.

* type L acc. to DIN 43710

Thermocouple - class 2, form B:

- 1 x type J
- 1 x type K
- other thermocouples: _____

Ring type:

- Ø 14 / 4,5 mm CuSn 6
- _____

Nominal length: _____ mm

Type:

- with kink protection (shrinkable sleeve)
- with fiberglass sleeve (shrinkable sleeve)

Connection cable:

(see also survey of connecting cables for thermocouples)

- extension cable strand/fiber glass/fiber glass/
stainless steel wire armouring +400°C
- extension cable strand/PFA/fiber glass/
stainless steel wire armouring +250°C
- _____

Cable length: _____ m

Connection ends:

- miniature thermoplug
- miniature socket
- standard plug
- Lemo plug type _____
- clips
- Lemo socket type _____
- bare ends
- other cable ends _____



The above mentioned technical data are standard data.

Individual parameters, e. g. connection cable, double thermocouple or cable end can be added or modified on request.

Other ring diameters on request.